

VALENCIA

BY QUBE

**Valencia Estate Design Guidelines
2025**



CONTENTS

INTRODUCTION

- 1.1 Welcome to Valencia
- 1.2 Purpose of the Design Guidelines
- 1.3 How to use the document
- 1.4 R-MD Codes
- 1.5 Local Development Plans
- 1.6 Compliance
- 1.7 Approval Process Flow Chat

HOUSE DESIGN & APPEARANCES

- 2.1 Style and character
- 2.2 The front elevation
- 2.3 Secondary elevation and corner lots
- 2.4 The roof
- 2.5 Colours and materials
- 2.6 Crossovers, driveways and garages
- 2.7 Laneways
- 2.8 Lot levels, retaining walls and drainage lot pit connections
- 2.9 Fencing and letterboxes
- 2.10 Outdoor areas and landscaping
- 2.11 Studios, ancillary accommodation, sheds, outbuildings, plant and equipment

SUSTAINABLE DESIGNS

- 3.1 Sustainable designs

GLOSSARY

- 4.1 Glossary

CHECKLIST

- 5.1 Builder Checklist

ANNEXURE A

- 6.1 City of Wanneroo Local Planning Policy 4.19 Medium Density Housing Standards (R-MD)

INTRODUCTION

1.1 WELCOME TO VALENCIA

Introducing Valencia Estate, a boutique land development in the heart of Wanneroo. Nestled in a well-established suburb rich with amenities, this unique estate draws inspiration from the vibrant beauty of fruit trees, creating a refreshing and tranquil environment for residents to enjoy.

With easy access to local shops, schools, and parks, Valencia Estate offers the perfect setting for your dream home. As the community grows and flourishes, Valencia Estate promises to be a place where nature, lifestyle, and connection come together, offering a welcoming, vibrant atmosphere for all.

1.2 PURPOSE OF THE DESIGN GUIDELINES

The Design Guidelines apply to all residential lots within Valencia and will help you and your chosen architect or builder to design a high quality home that fits in with the aesthetic of the estate.

The appearance of housing, front yards and verges contribute to community pride and property values allowing you to have confidence in your investment.



1.3 HOW TO USE THE DOCUMENT

The Design guidelines include mandatory elements that must be complied with and recommended design elements you are strongly encouraged to consider.

To ensure your home meets the requirements of the Design Guidelines, your Contract of Sale specifies that you must submit your preliminary design for Developer approval prior to lodging plans with the City of Wanneroo. A checklist for mandatory requirements has been included at the end of this document.

1.4 R-MD CODES

In addition to these Design Guidelines, the City of Wanneroo's Local Planning Policy 4.19 Medium Density Housing Standards (R-MD) applies to all lots within Valencia.

The purpose of LPP 4.19 is to replace the deemed to comply requirements of the following clauses of the R-Codes with those set out in the provisions of this policy:

- Building and Garage setbacks – Clauses 5.12, 5.13 and 5.21;
- Open Space – Clause 5.1.4;
- Parking – Clause 5.3.3;
- Visual Privacy – Clause 5.4.1; and
- Solar Access – Clause 5.4.2.

A copy of the LPP 4.19 is included as Annexure A to the Design Guidelines.

1.5 LOCAL DEVELOPMENT PLANS

In addition to these Design Guidelines, a Local Development Plan (LDP) has been prepared over a small number of lots within Valencia. The LDP sets out permissible variations to the Residential Design Codes and R-MD Codes that have been adopted by the City of Wanneroo. Compliance with the LDP is assessed by the City of Wanneroo as part of your application for Development Approval and/or Building License.

The LDP's identify requirements for:

- Dwelling orientation;
- Outdoor living areas;
- Vehicle access and the location of garages; and
- Windows that address the neighbouring park.

A copy of the LDP should it apply to your lot is provided within your Contract of Sale.

1.6 COMPLIANCE

Developer Approval ensures all homeowners meet the Design Guidelines mandatory requirements. Compliance with mandatory design measures (Design Requirements) is a contractual obligation. City of Wanneroo approval ensures compliance with statutory and policy requirements.

The Design Guidelines must be read in conjunction with Valencia Local Development Plan as approved by the City of Wanneroo, local laws and Policies, Residential Design Codes of Western Australia (R Codes) and other statutory requirements. QUBE does not warrant the City of Wanneroo will approve a house plan if it satisfies these Design Guidelines.

1.7 APPROVAL PROCESS FLOW CHART

The Design Guidelines apply to all residential lots within Valencia and will help you and your chosen architect or builder to design a high quality home that fits in with the aesthetic of the estate.

The appearance of housing, front yards and verges contribute to community pride and property values allowing you to have confidence in your investment.

Applicants must provide the following and should be lodged electronically in PDF format to QUBE's online portal which is accessible via QUBELand.com.au/buildersportal

Site Plan

Include levels, location of dwelling and garage, boundary setbacks, all fences,

retaining walls and other outbuildings or structures.

Floor Plan

The proposed house design and room layout, including window and door locations, alfresco areas, etc.

Elevations

Materials and colours schedule for walls, the roof and trims. Ceiling height of front rooms (if single storey) are to be shown as well as roof pitch.

Landowners are responsible for checking whether any of the following items apply prior to design;

- A Local Development Plan
- Geotechnical soil classification (may require special design)
- Existing infrastructure such as retaining walls, fences, utilities, or similar
- Bushfire Management Plan

Step 1: Review

Review your Contract of Sale & the Design Guidelines (DG's) & Local Development Plans (LDP's) to understand the requirements for your house and land.

Step 2: Design

Work with your architect or builder to prepare a preliminary design that meets the requirements of the DG's and the LDP's.

Step 3: Developer Submissions

Submit design drawings to the developer.

Does not meet the requirements

The Developer will provide components to assist you with meeting the requirements. The design will need to be amended and re-submitted in order to qualify for your fencing and front landscaping rebate.

Step 4: Developer Assessment

QUBE assess the design against the DG's.

Step 7: City of Wanneroo Approval

CoW provides approval for the house design. All approvals now achieved for the construction to commence on your new home.

Step 6: City of Wanneroo (CoW) Assessment

Submit design drawings to CoW for development approval/building license.

Step 5: Developer Approval

QUBE provides approval against the DG's.



HOUSE DESIGN AND APPEARANCES



2.1 STYLE & CHARACTER

Housing should be aspirational and reflect the surrounding natural features. Contemporary trends and sound environmental practices are promoted.

Be inspired by Valencia parklands and streets as you make external colour selections.

2.2 FRONT ELEVATION

The front elevation makes the greatest contribution to maintaining a consistent visual aesthetic across Valencia Estate.

It also helps protect your family's asset should you choose to sell in the future. This can be achieved by ensuring that the following requirements are incorporated in the design of your new home.

Mandatory Requirements

- The front of your home must contain the front door and have windows with a clear view of the street. The front door must not be accessed from the garage.
- A veranda, portico or porch must be provided to the front of the house to create an open and welcoming entry for your home. This should be a minimum of 1.2m in depth and have the same design qualities and character as the home.
- At least one of the following architectural elements are to be incorporated:
 - o Gable
 - o Roof gable (dutch gable)

- o Bay window
- o Balcony
- o Planter box
- o Blade or feature wall
- o Corner window
- o Other feature approved by QUBE
- The majority of the front elevation must have eaves with a minimum depth of 450mm, except the garage. At the developer's discretion, an architectural element that is an integral part of the facade and which projects forward at least 450mm from the facade, may be considered in lieu of an eave, subject to that architectural element providing shade protection to a major opening.
- Include at least 450mm articulation in floor plan and roof plan required for primary elevation (excluding garage for 15m frontages and above), however for lots less the garage can be included.



- Include at least two different materials provided each material used comprises no less than 15% of total front elevation wall. (Excluding doors, windows and roof). The use of two renders does not satisfy this requirement.
- One of the materials (mentioned below) must be provided in the front elevation of your home (excludes door and window treatments, roof and garage doors):

- o Rendered brickwork
- o Feature tiling
- o Stone cladding
- o Timber cladding
- o Other feature approved by QUBE
- o Plain fibre cement sheeting will not be accepted as a suitable material

Individuality, architectural expression and innovation are promoted. Alternative designs will be considered where Valencia vision is maintained. Approval of alternative designs does not set a precedent and is entirely at the discretion of the developer.

Window roller shutters are not permitted on the primary frontage.

boundary fence) with the same design qualities and character to enhance street appeal. For example, if the front facade is primarily render, then only render of the same colour can be used as the finish that extends along the side street elevation for a length of 2m.

Encouraged Requirements

- The exposed secondary street façade must incorporate at least one major opening as defined under the R Codes.
- Verandas extending from the front of the home around to the secondary elevation, and windows that increase neighborhood security are encouraged.

2.3 SECONDARY ELEVATION & CORNER LOTS

PROVIDING “PASSIVE SURVEILLANCE” IS AN IMPORTANT CONTRIBUTOR TO PEOPLE’S PERCEPTION OF THEIR SAFETY AND THE COMMUNITY’S SAFETY.

Mandatory Requirements

You will need to consider the following requirements when designing your home:

- The appearance of the front façade must extend to the side street on corner lots.
- The main colour and materials used on the primary elevation must ‘wrap’ around the corner for the portion of the home visible from the street (2m from the side wall forward of the



2.4 THE ROOF

THE ROOF IS AN IMPORTANT ELEMENT OF YOUR HOME'S ARCHITECTURAL CHARACTER. IF DESIGNED EFFECTIVELY IT WILL IMPROVE THE ENVIRONMENTAL PERFORMANCE OF YOUR HOUSE, AS WELL AS PROVIDING SPACE FOR SOLAR HOT WATER UNITS AND PHOTOVOLTAIC PANELS.

Mandatory Requirements

To achieve this it must meet the following criteria:

- Skillion roofs to have a minimum pitch of 5 degrees and a maximum pitch of 15 degrees.
- Traditional pitched hip and valley roof form:
- Lots with a frontage greater than 10m to the primary street - roof form pitched at an angle greater than 22 degrees.
- Lots with a frontage equal to or less than 10m to the primary street - roof form pitched at an angle greater than 24 degrees.
- Must be constructed in a single material and colour.
- Gutters and downpipes must compliment the home.
- Highly reflective roof tops such as ZINCALUME® are not permitted.



Encouraged Requirements

- A light coloured roof is encouraged to reduce solar absorbency and energy usage.
- Coloured pre-finished corrugated metal sheeting and low profile roof tiles are encouraged.

2.5 COLOURS AND MATERIALS

COLOUR PALETTE IS NOT RESTRICTED AND VARIATIONS IN COLOUR AND TEXTURE ARE PROMOTED, HOWEVER TONES SHOULD BE COMPLIMENTARY, TAKE CUES FROM THE LOCAL LANDSCAPE AND EXPRESS INDIVIDUALITY THROUGH CAREFULLY CHOSEN ACCENTS.

Mandatory Requirements

- Avoid the use of primary and vivid colours and reflective surfaces.

Encouraged Requirements

- The use of lighter tones is promoted. Bold and dark colours are best used in small sections against a neutral or subdued backdrop.

2.6 CROSSOVERS, DRIVEWAYS AND GARAGES

STREETSCAPE AND SECURITY IS ENHANCED THROUGH THE CAREFUL DESIGN OF YOUR CROSSOVERS, DRIVEWAYS AND GARAGES.

Mandatory Requirements

You will need to consider the following requirements when designing your home:

- Your driveway must be constructed

from brick paving, liquid limestone or exposed aggregate concrete. Grey or painted concrete is not permitted.

- Public footpaths take priority over private vehicular access therefore driveways must not cut-through paths, unless otherwise mandated by city of Wanneroo.
- The location of your garage has taken into account where the crossover and driveway will go to avoid the removal of street trees or conflicts with service infrastructure such as power domes.
- Laying an appropriate conduit pipe under the driveway has been included in your plans to ensure landscape irrigation can be installed.
- Only side by side double garages with a minimum internal width of 5.4m are permitted. Single garages are not permitted. Triple garages are permitted subject to the third garage being setback 0.5m behind the main (double) garage, and subject to the developer's approval.
- All garages shall be enclosed with a door and installed prior to occupation.
- Car ports are not permitted.

Encouraged Requirements

- Internal garage storage is encouraged.



2.7 LOT LEVELS, RETAINING WALLS & DRAINAGE LOT PIT CONNECTIONS

YOUR LOT LEVELS AND RETAINING WALLS HAVE BEEN DESIGNED, CONSTRUCTED AND CERTIFIED TAKING INTO ACCOUNT SITE CLASSIFICATION AND DRAINAGE REQUIREMENTS. THEREFORE IT IS IMPORTANT THE FOLLOWING COMPLY:

Mandatory Requirements

- Lot levels are set as part of estate works and should not be modified by more than 200mm.
- Modifications to retaining walls installed by the Developer are not allowed unless for maintenance or where written approval by the Developer and the City of Wanneroo has been granted.
- It is important you pass on this information to your builder when designing your new home.

2.8 FENCING AND LETTERBOXES

Mandatory Requirements

- Installing a front fence is not permitted.
- Fencing is not permitted within the front setback area of a lot (including forward extensions of side boundary fencing and fencing on corner truncations), regardless of the relevant R-MD Code provisions.
- Side and rear boundary fencing must be 1.8m high estate 'Monument' Colorbond fencing. The finish of

any side or rear boundary gates should complement the fence.

- Corner lots side fencing must be installed two metres back from the forward most point of the closest wall of your home to the boundary or behind the corner stone pier should your lot have one. Please take this into consideration when selecting the front rooms due to any privacy concerns you may have.

By submitting your plans and gaining the Developer's approval (and meeting the terms and conditions of your contract), will allow you to claim the Valencia Estate fencing rebate.

Encouraged Requirements

- Your letterbox should be constructed from materials similar to, or complementary to your home.



2.9 LANDSCAPING

WELL-DESIGNED FRONT YARD AND VERGE AREAS CAN INCREASE PRIVACY, ENERGY EFFICIENCY, WATER EFFICIENCY AND IMPROVE THE PRESENTATION OF YOUR HOME AND YOUR FAMILY'S ASSET. STREET TREES CAN TRANSFORM THE CHARACTER OF STREETS AND PROVIDE NUMEROUS ENVIRONMENTAL AND AESTHETIC BENEFITS, INCLUDING HELPING TO INCREASE THE VALUE OF YOUR HOME.

Mandatory Requirements

- At Valencia, each homeowner as part of the front landscaping and verge rebate will be provided with at least one mandatory street tree in the verge.
- Homeowners to provide reticulation to verge areas, complete landscaping prior to occupation and continue to maintain lawn and garden areas.

Encouraged Requirements

- Your landscape design and plant selection should respond to local conditions and homeowners are encouraged to consider native and water-wise options.

- We encourage you to plant more trees within your own landscaping.

By submitting your plans and gaining the Developer's approval (and meeting the terms and conditions of your contract), will allow you to claim the Valencia estate front landscaping rebate.



2.10 STUDIOS AND ANCILLARY ACCOMMODATION, SHEDS, OUTBUILDINGS, PLANT AND EQUIPMENT

Mandatory Requirements

- Studios and ancillary accommodation should be constructed in complementary materials and colours to your home.
- Any shed, storeroom, outbuilding or other freestanding structure should be located in your backyard to minimize visibility from adjacent streets, and parks and constructed in materials and colours that complement your home.
- For Corner lots, sheds and outbuildings shall not extend 500mm above fences and shall not be greater than 10sqm in floor area unless approved by City of Wanneroo
- Building services such as air-conditioning units, satellite dishes, TV antennae, solar hot water units and photovoltaic panels must be screened from public view or located in the least visibly obtrusive location from adjacent streets, and parks.
- Clothes drying areas must be screened from view from adjacent streets, laneways and parks. They should be well located to access sunlight and breezes.
- Bin storage areas must be screened from view from adjacent streets, laneways and parks.. Location of bin storage to be indicated on submitted plans.
- For narrow lots (10.5m frontage or less) where there are boundary walls both sides and no access through the garage to a suitable area, bin screening will need to be provided by some other means, usually within the garage. This could be achieved by providing a minimum garage dimension of 6.0m x 6.0m.
- A chemical toilet must be used during the construction of your home and this must be serviced by an approved tankering service. The toilet must not be connected to any part of the sewerage system.

Encouraged Requirements

- Photovoltaic panels and solar hot water units should be positioned to access northern and western sunlight and should be integrated with the roof profile of the home and not elevated at any angle to the roof pitch.
- Building services should be finished in a similar colour to the roof and located to minimize potential nuisance, such as noise to neighbouring properties.



3.1 SUSTAINABLE DESIGNS

A home designed to suit lot and local conditions can enhance comfort, ease household energy and water costs and provide long term environmental benefit.

Information about climate responsive design including solar access, natural ventilation, thermal and water efficiency can be obtained from;

www.yourhome.gov.au

www.water.wa.gov.au

Valencia provides good access to natural light, views and cooling breezes. Simple items to consider when planning your home include;

- Orientating important internal living areas such as the kitchen, family room or lounge to have access to northern winter sun
- Protecting north and west facing rooms from summer sun through shading devices, deeper eaves or appropriate plantings
- Where possible placing garages in a western or eastern location to insulate against the summer sun
- Placing window openings to increase natural airflow, particularly through key living spaces
- Zoning internal living and sleeping areas to allow for localised heating and cooling
- Locating hot water systems as close as possible to the kitchen and main bathroom

QUBE reserves the right to amend Valencia Design Guidelines at any point in time.



4.1 GLOSSARY



Articulated Façade	Variations to the elevation through projections and indentations in the floor plan and roof.
Awning	A roof structure supported by a frame and located over a window to provide shade.
Corner Lot	A lot with more than one street front boundary.
Corner Truncation	The angular portion of a street front boundary.
Eaves	A roof overhang that provides shading to a wall face.
Elevation	An external wall of any part of a dwelling facing a boundary.
Estate Works	Structures and works undertaken as part of subdivision construction.
Façade	The face of a building, typically the primary street elevation showing its most prominent architectural features.
Front Facing	Any fencing forward of the main building line.
Gable	A triangular top section of a wall on a building with a pitched/skillion roof.
Habitable Room	All living rooms, kitchens, bedrooms, activity rooms and studies.
Main Building Line	Is measured from the front most habitable room on the primary street elevation, not the projection of a feature.
Porch	An overhanging area of roof created through an indentation in the floor plan, usually where a door is located.
Portico	An entry feature with a separate roof and supported by posts, pillars or piers.
Primary Street	The street providing main pedestrian access to the dwelling.
Public View Streets	An area in view from common spaces such as parkland or streets.
R-Codes	Western Australian Planning Commission's Residential Planning Codes.
R-MD Codes	Medium-density single house development standards.



CHECKLIST

5.1 BUILDER CHECKLIST

HOUSE DESIGN

Front Elevation (as determined by the Developer)

- ☐ The front of your home must contain the front door and have windows with a clear view of the street. The front door must not be accessed from the garage.
- ☐ A veranda, portico or porch must be provided to the front of the house to create an open and welcoming entry for your home. This should be a minimum of 1.5m in depth and have the same design qualities and character as the home.
- ☐ At least one of the following architectural elements are to be incorporated:
 - ☐ Gable
 - ☐ Roof gable (dutch gable)
 - ☐ Bay window
 - ☐ Balcony
 - ☐ Planter box
 - ☐ Blade or feature wall
 - ☐ Other feature approved by QUBE
- ☐ The majority of front elevation must have eaves with a minimum depth of 450mm, except the garage.
- ☐ Include at least 450mm articulation in floor plan and roof plan required for primary elevation (excluding garage for 15m frontages and above, however for lots less the garage can be included).
- ☐ Include at least two different materials provided each material used comprises no less than 15% of total front elevation wall. (Excluding doors, windows and roof).
- ☐ One of the following materials (mentioned above) must be provided in the front elevation of your home (excludes door and window treatments, roof and garage doors):

- ☐ Rendered brickwork
- ☐ Feature tiling
- ☐ Stone cladding
- ☐ Timber cladding
- ☐ Other feature approved by QUBE

Secondary Elevation and Corner lots

- ☐ The appearance of the front façade must extend to the side street on corner lots.
- ☐ The main colour and materials used on the primary elevation must 'wrap' around the corner for the portion of the home visible from the street (2m from the side wall forward of the boundary fence) with the same design qualities and character to enhance street appeal.
- ☐ The exposed secondary street façade must incorporate at least one major opening as defined by the R Codes .

Roof

- ☐ Skillion roofs to have a minimum pitch of 5 degrees and a maximum pitch of 15 degrees.
- ☐ Traditional pitched hip and valley roof form:
- ☐ Lots with a frontage greater than 10m to the primary street - roof form pitched at an angle greater than 22 degrees.
- ☐ Lots with a frontage equal to or less than 10m to the primary street - roof form pitched at an angle greater than 24 degrees.
- ☐ Must be constructed in a single material and colour.
- ☐ Highly reflective roof tops such as ZINCALUME® are not permitted.

Colours and Materials

- ☐ Avoid the use of primary and vivid colours and reflective surfaces.

- ☐ Colour and material palette must be provided on front elevation plans for developer approval (includes walls, roof and trims).

Crossovers, Driveways and Garages

- ☐ Your driveway must be constructed from brick paving, liquid limestone or exposed aggregate concrete. Grey or painted concrete is not permitted.
- ☐ Public footpaths take priority over private vehicular access therefore driveways must not cut-through paths unless mandated by City of Wanneroo Wanneroo
- ☐ The location of your garage has taken into account where the crossover and driveway will go to avoid the removal of street trees or conflicts with service infrastructure such as power domes.
- ☐ Laying an appropriate conduit pipe under the driveway has been included in your plans to ensure landscape irrigation can be installed.
- ☐ Garages are not to be forward of the dwelling alignment.
- ☐ Garages are to be setback 1.5m from the secondary street.
- ☐ Only side by side double garages with a minimum internal width of 5.4m are permitted. Single garages are not permitted. Triple garages are permitted subject to developer's approval.
- ☐ All garages shall be enclosed with a door and installed prior to occupation.

Lot Level

- ☐ Lot levels have not been modified by more than 200mm.

Fencing

- ☐ Fencing is not permitted within the front setback area of a lot (including forward

extensions of side boundary fencing and fencing on corner truncations) regardless of the relevant PMD provisions.

- ☐ Please be aware corner lots side fencing must be installed two metres back from the forward most point of the closest wall of your home to the boundary or behind the corner stone pier should you lot have one. Please take this into consideration when selecting the front rooms due to any privacy concerns you may have.

Front Landscaping and Verge Planting

- ☐ Please be aware that each homeowner as part of the front landscaping and verge rebate will be provided with at least 1 mandatory street tree in the verge. The street tree will be installed by the City of Wanneroo once the landscape package has been installed by the Developer.

Sheds and Outbuildings

- ☐ For Corner lots, sheds and outbuildings shall not extend 500mm above fences and shall not be greater than 10sqm in floor area unless approved by City of Wanneroo.

Plant and Equipment

- ☐ Building services such as air-conditioning units, satellite dishes, TV antennae, solar hot water units and photovoltaic panels must be screened from public view or located in the least visibly obtrusive location from adjacent streets, laneways and parks.
- ☐ Clothes drying areas must be screened from view from adjacent streets, laneways and parks. They should be well located to access sunlight and breezes.
- ☐ Bin storage areas must be screened from view from adjacent streets, laneways and parks and indicated on submitted drawings..
- ☐ On narrow lots (10.5m frontage or less) where there are boundary walls both sides and no access through the garage to a suitable area,

bin screening will need to be provided by some other means, usually within the garage. This could be achieved by providing a minimum garage dimension of 6.0m x 6.0m.

Other Important Items

- ☐ Checked for the existence of a Local Development Plan, special Geotechnical requirements, Bushfire Management reports, BAL ratings and/or infrastructure items that may impact design.
- ☐ Site plan, floor plan and elevations included within the application for Developer Approval.
- ☐ A chemical toilet must be used during construction, with its designated location marked on a site plan.



ANNEXURE A



Owner	Planning and Sustainability
Implementation	18 July 2023
Next Review	16 October 2024

POLICY OPERATION

Policy Development

This Policy has been prepared under the provisions of Clause 3 of the deemed provisions of the City of Wanneroo District Planning Scheme No. 2 (DPS 2).

Application and Purpose

This policy replaces the R-Code provisions for Medium Density Housing within development zones. This Policy replaces the deemed-to-comply provisions of the following clauses of the Residential Design Codes with those set out in the provisions of this policy:

- Building and garage setbacks – clauses 5.12, 5.13 and 5.21
- Open space – clause 5.1.4
- Parking – clause 5.3.3
- Visual Privacy – clause 5.4.1
- Solar Access – clause 5.4.2

This policy will apply where the approved structure plan identifies that the R-MD standards applies. The Policy provisions also apply to all subdivision applications lodged or approved after 8 May 2015, where applicable and subject to the Structure Plan stating that they will apply.

All other R-Codes standards will continue to apply.

The WAPC has stated that they generally will not support further variations to the R-MD provisions and will only support innovative housing typologies (not considered in the typical lot size / type in Appendix 1) that deliver positive community outcomes.

Definitions

- Approved Structure Plan:** A structure plan or activity centre plan that has been approved by the WAPC under Part 4 or Part 5 of DPS 2.
- Front Load:** Lots where the primary vehicle access is via the front of the lot and the garage / carport is located at the front of the dwelling.
- Medium Density:** R25-R60 density codes.

- **Rear Load:** Lots where the primary vehicle access is via the rear of the lot, from a street or right of way (ROW) and the garage / carport is located at the back of the dwelling.
- **R-MD / R-MD Codes:** Single House standards for medium density housing.

Objectives

The objectives of this policy are to:

- 1) Ensure consistent application of variations to the deemed-to-comply provisions of the R Codes to medium-density single houses located in development zones;
- 2) Reflect changes in housing trends on smaller lots and adequately respond to market pressures; and
- 3) Provide a mechanism which allows the WAPC adopted R-MD provisions to be implemented.

GENERAL POLICY PROVISIONS

The general policy provisions are detailed in Appendix 1 as follows:

Single house standards for medium density housing in development zones (R-MD Codes)

R-Code	Lot type and size	Street setback and front fences		Lot boundary setback		Open space		Garage setback and width and vehicular access		Parking		Overshadowing		Privacy	
		R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision
R-MD – R60	Rear load 5m x 30m – 150m² 6m x 30m – 180m² Front load 8.5m x 20m – 170m² 7.5m x 25m – 187.5m²	2m	2m minimum, no average 1m to porch / veranda no maximum length 1m minimum to secondary street Front fences within the primary street setback area being a maximum height of 900mm above natural ground level, measured from the primary street side of the front fence	Boundary setbacks 1 to 1.5m for wall height 3.5m and less (subject to wall length and major openings) Boundary walls 2/3 length one side boundary, max 3.5m high and 3m average height	Boundary setbacks 1.2m for wall height 3.5m or less with major openings 1m for wall height 3.5 or less without major openings Boundary walls No maximum length to both side boundaries	40% open space (60% site cover) 16m ² courtyard 1/3 required outdoor living area (OLA) may be covered Minimum dimension 4m	An outdoor living area (OLA) with an area of 10% of the lot size or 20m ² , whichever is greater, directly accessible from a habitable room of the dwelling and located behind the street setback area At least 70% of the OLA must be uncovered and includes areas under eaves which adjoin uncovered areas The OLA has a minimum 3m length or width dimension No other R-Codes site cover standards apply	Rear load Nil – provided laneway is minimum of 6m wide Front load 4.5m or 0.5m behind dwelling alignment subject to averaging requirements Garage width limited to maximum 50% of lot frontage where garage in front of or within 1m of building	Rear load 0.5m garage setback to laneway Front load 4.5m garage setback from the primary street and 1.5m from a secondary street For front loaded lots with street frontages between 10.5 and 12m, a double garage is permitted to a maximum width of 6m as viewed from the street subject to: - A major opening to a habitable room directly facing the primary street - An entry feature consisting of a porch or veranda with a minimum depth of 1.2m; and - No vehicular crossover wider than 4.5m where it meets the street Lots with a frontage less than 10.5m or not compliant with above require single or tandem garaging	Two on-site bays	One on-site bay where dwelling has two bedrooms or less	50% of the adjoining site area	No maximum overshadowing	3m to bedrooms and studies 4.5m to all other major openings 6m to balconies or similar	No privacy provisions apply
R-MD – R40	Rear load 7.5m x 30m – 225m² Front load 8.5m x 30m – 255m² 8.5m x 25m – 212.5m² 10 x 20m – 200m² 10 x 25m – 250m² 12.5m x 20m – 250m²	4m	2m minimum, no average 1.5m to porch / veranda no maximum length 1m minimum to secondary street Front fences within the primary street setback area being a maximum height of 900mm above natural ground level, measured from the primary street side of the front fence	Boundary setbacks 1 to 1.5m for wall height 3.5m and less (subject to wall length and major openings) Boundary walls 2/3 length one side boundary, maximum 3.5m high and 3m average height	Boundary setbacks As per R-MD – R60 Boundary walls To both side boundaries subject to: No maximum length to one side boundary, 2/3 max length to second side boundary for wall height 3.5m or less	45% open space (55% site cover) 20m ² courtyard 1/3 required OLA area may be covered Minimum dimension 4m	As per R-MD – R60	Rear load Nil – provided laneway is minimum of 6m wide Front load 4.5m or 0.5m behind dwelling alignment subject to averaging requirements	As per R-MD – R60	Two on-site bays	As per R-Codes	35% of the adjoining site area	No maximum overshadowing for wall height 3.5m or less No maximum overshadowing for wall height greater than 3.5m where overshadowing is confined to the front half of the lot. If overshadowing intrudes into rear half of the lot, shadow cast does not exceed 35%	4.5m to bedrooms and studies 6m to all other major openings 7.5m to balconies or similar	R-Codes clause 5.4.1 C1.1 applies, however the setback distances are 3m to bedrooms and studies, 4.5m to major openings to habitable rooms other than bedrooms and studies and 6m to unenclosed outdoor active habitable spaces

Appendix 1

Single house standards for medium density housing in development zones (R-MD Codes)

R-Code	Lot type and size	Street setback and front fences		Lot boundary setback		Open space		Garage setback and width and vehicular access		Parking		Overshadowing		Privacy	
		R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision
R-MD – R30	Rear load 10m x 30m – 300m ² Front load 10m x 30m – 300m ² 15m x 20m – 300m ²	4m	2m minimum, no average 1.5m to porch / veranda no maximum length	Boundary setbacks 1 to 1.5m for wall height 3.5m and less (subject to wall length and major openings) Boundary walls 2/3 length one side boundary, maximum 3.5m high and 3m average height	Boundary setbacks As per R-MD – R60 Boundary walls to both side boundaries subject to: 2/3 length to one side boundary, 1/3 max length to second side boundary for wall height 3.5m or less	45% open space (55% site cover) 24m ² courtyard 1/3 required OLA area may be covered Minimum dimension 4m	As per R-MD – R60	Rear load Nil – provided laneway is minimum of 6m wide Front load 4.5m or 0.5m behind dwelling alignment subject to averaging requirements	As per R-MD – R60	Two on-site bays	As per R-Codes	35% of the adjoining site area	As per R-MD – R40	4.5m to bedrooms and studies 6m to all other major openings 7.5m to balconies or similar	As per R-MD – R40
R-MD – 25	Front load 12.5m x 25m – 312.5m ² 15m x 25m – 375m ² 12.5m x 30m – 375m ²	6m	3m 1.5m to porch / veranda no maximum length 1.5m minimum to secondary street Front fences within the primary street setback area being a maximum height of 900mm above natural ground level, measured from the primary street side of the front fence	Boundary setbacks 1 to 1.5m for wall height 3.5m and less (subject to wall length and major openings) Boundary walls 2/3 length one side boundary, max 3.5m high and 3m average height to one side boundary	Boundary Setbacks As per R-MD – R60 Boundary walls As per R-MD – R30	50% open space (50% site cover) 30m ² courtyard 1/3 required OLA area may be covered Minimum dimension 4m	As per R-MD – R60	Rear load Nil – provided laneway is minimum of 6m wide Front load 4.5m or 0.5m behind dwelling alignment subject to averaging requirements	As per R-MD – R60	Two on-site bays	As per R-Codes	25% of the adjoining site area	As per R-MD – R40, however if overshadowing intrudes into rear half of the lot, shadow cast does not exceed 25%	4.5m to bedrooms and studies 6m to all other major openings 7.5m to balconies or similar	As per R-MD – R40